

MECHANICAL REQUIREMENTS

MAGAZINE TRIM SIZE
7.875" x 10.5"

BINDING METHOD
Saddle Stitch

PRINTING PROCESS
Web Offset

	BLEED	NON-BLEED
SPREAD	16" x 10.75"	15.375" x 10"
FULL PAGE (W/ COVERS)	8.125" x 10.75"	7.375" x 10"

*KEEP LIVE MATTER 1/4" FROM THE FINAL TRIM.

FILE SPECIFICATIONS

▶ PDF x-1a: Acrobat 4.0 and up (PDF 1.3 all fonts embedded-use press options)

▶ **ACCEPTED PROOFS**

Digital halftone: Kodak Approval with color bars.

Inkjet: Iris or Dupont Waterproof with color bars, 2 proofs to accompany each ad.

▶ **SPECIAL INSTRUCTIONS**

Build page to trim and extend bleed beyond page edge. Do NOT apply style attributes. All elements to be placed at 100% with no rotation or cropping. Pantone colors must be in CMYK mode. DPI = 2400

▶ **FONT INFORMATION**

Font information should include manufacturer, font name and version. Use stylized fonts and do not apply style attributes to basic fonts.

▶ **PORTAL**

Ad Shuttle
<http://www.adshuttle.com/theweek>

▶ **COLOR CALIBRATION**

SWOP standards, GATF/SWOP-approved scales, targets and control patches. Include 5%, 25%, 50%, 95% and 100% Cyan, Yellow, Magenta and Black control patches.

▶ **SEND MATERIALS TO**

Advertising Production Department
THE WEEK Publications Inc.
55 West 39th Street, 5th Floor
New York, NY 10018

▶ **PRODUCTION QUESTIONS**

Kyle Christine Darnell
646.717.9558 | kydarnell@qg.com